

# SAFETY JOGGER

PROFESSIONAL

Heavy

## BESTLIGHT1 OB

**Ultra-Light, Sterilizable Medical Shoes for Ultimate Comfort**

BESTLIGHT1 medical shoes offer superior comfort and hygiene. With a tight grip for slippery surfaces, these lightweight, easy-to-clean shoes support chemical, UV, and machine washing at 30°C.

|               |   |
|---------------|---|
| Upper         | Expanded EVA  |
| Lining        | N/A   |
| Footbed       | SJ Basic 2  |
| Outsole       | EVA/Rubber (NBR)  |
| Category      | OB / SRC  |
| Size range    | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0<br>JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.197 kg  |
| Norms         | EN ISO 20347:2012   |



BLK



WHT



**Washable 30°C**  
These shoes can be washed in a washing machine at 30°C.



**Chemically & UV sterilizable**  
This shoe is chemically and UV sterilizable.

**Industries:**

Catering, Chemical, Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment, Extreme slippery surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                                     | Measure unit          | Result      | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Expanded EVA</b>                             |                       |             |              |
|                | Upper: permeability to water vapor              | mg/cm <sup>2</sup> /h | N/A         | ≥ 0.8        |
|                | Upper: water vapor coefficient                  | mg/cm <sup>2</sup>    | N/A         | ≥ 15         |
| <b>Lining</b>  | <b>N/A</b>                                      |                       |             |              |
|                | Lining: permeability to water vapor             | mg/cm <sup>2</sup> /h | N/A         | ≥ 2          |
|                | Lining: water vapor coefficient                 | mg/cm <sup>2</sup>    | N/A         | ≥ 20         |
| <b>Footbed</b> | <b>SJ Basic 2</b>                               |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles) | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>EVA/Rubber (NBR)</b>                         |                       |             |              |
|                | Outsole abrasion resistance (volume loss)       | mm <sup>3</sup>       | 83.0        | ≤ 150        |
|                | Outsole slip resistance SRA: heel               | friction              | 0.45        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat               | friction              | 0.46        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel               | friction              | 0.22        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat               | friction              | 0.32        | ≥ 0.18       |
|                | Antistatic value                                | MegaOhm               | N/A         | 0.1 - 1000   |
|                | ESD value                                       | MegaOhm               | N/A         | 0.1 - 100    |
|                | Heel energy absorption                          | J                     | N/A         | ≥ 20         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.