

PRODRY 2131X

The all-in-one safety gloves with double latex coating

The seamless water repellent PRODRY gloves of Safety Jogger are designed for activities in every environment and for every weather condition. The polyester/nylon liner is provided with a fully latex coating (sky blue colour) and a second roughened latex coating (black colour) on the palm of the hand. Polyester/nylon liner with maximum comfort. Keeps your hands dry in wet working conditions. Isolating foam latex coating against cold weather conditions.

Performance level	2131X
Liner	15 GAUGE POLYESTER
Coating	LATEX
Size range	EU 7-12
Norms	EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry, Tactical



BLB

Performance level 2131X

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- Tear resistance: based on the amount of force required to tear the sample.
- Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.