



Heavy

PROMOALASK S3

Winterbox including the Alaska safety boot

Winterbox including 1 pair of Alaska safety boots, 1 pair of socks, 1 pair of winter working gloves and a warm Safety Jogger beanie

| | |
|---------------|---|
| Upper | Pull-up Action Leather |
| Lining | Teddy |
| Footbed | Teddy |
| Midsole | Steel |
| Outsole | PU |
| Toecap | Steel |
| Category | S3 / SRC, CI |
| Size range | EU 38-47 / UK 5.0-12.0 / US 5.5-13.0 JPN 24-31 / KOR 250-310 |
| Sample weight | 0.853 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



BRN



Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Warm lining

Keeps your feet warm and dry in cold environments.



Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

Industries:

Automotive, Chemical, Construction, Logistics, Mining, Oil & Gas, Industry

Environments:

Cold environment, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Pull-up Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 7.1 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 64 | ≥ 15 |
| Lining | Teddy | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 120.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 964.8 | ≥ 20 |
| Footbed | Teddy | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 85.1 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.40 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.42 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 108.7 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 30 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 15.0 | ≥ 14 |

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.